

*The Monimax 5300CE offers powerful financial-transaction support. This high-volume ATM solution has a large cash capacity that gives customers reliable 24/7 access.*

## **Features**

### **TCP/IP with SSL Support**

Monimax 5300CE includes built-in TCP/IP with Secure Socket Layers (SSL) for extra security while connected to the Internet. This new connectivity feature provides a direct connection without additional boxes, adaptors or converters. The result? A more efficient product that saves both time and money.

### **Capacity from 1,000 to 8,000 Notes**

Customize a dispenser profile based on the volume of transactions at each Monimax 5300CE site. This scalable ATM is an ideal solution for multiple locations with various dispenser needs. Configuration can include up to four 2,000-note cassettes for a maximum of 8,000 notes.

### **Sophisticated Design**

Featuring an easy-to-use 15" LCD display, bright lead-through indicator and an ergonomic design, the Monimax 5300CE is a smart choice for its small size and powerful functions.

***Superior quality, security and value.  
Only with Nautilus Hyosung.***



**Experience a totally new ATM with Monimax 5300CE.**

### **Dependable Customer Service**

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

# MONIMAX 5300CE

## System Control

- Intel® Xscale® processor
- Microsoft® Windows CE® platform

## Communication

- TCP/IP (SSL configurable)

### Optional

- Dial-up, Wireless

## Customer Display

- 15" TFT LCD

### Optional

- Privacy filter

## Input Type

- 4 x 2 function keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

## Card Handling

- Dip-type card reader
- Optional IC card reader, EMV Level 1, 2 compliant

## Cash Dispensing

- 2,000-note cassette
- Up to four cassettes (8,000 notes)

## Printers

- 3.1" graphical thermal receipt printer
- 3,500 transactions
- Electronic journal

## Security

- UL291 business hour safe

### Optional

- UL291 Level 1 safe
- Electronic safe lock (standard)
- KABA Mas Cencen safe lock
- Security camera

## Miscellaneous

- Lead-through indicator

## Power Supply

- AC 110–240V, 50–60 Hz

## Operating Environment

- Temperature: 28°F–104°F
- Humidity: 25%–85%

## Dimension and Weight

- Height: 54.4" (1,381.9 mm)
- Width: 18.1" (460 mm)
- Depth: 25.4" (644 mm)
- Weight: 617 lbs (280 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



3.1" graphic thermal receipt printer

Key pad light

PCI EPP



Security camera (optional)

15" color customer display  
• Optional sunlight viewable

4 x 2 function keys

Lead thru indicator  
Card reader

Cash dispenser

 NAUTILUS HYOSUNG

Contact your authorized Nautilus Hyosung distributor or representative for more information.